

Aerospace Adhesives

NEW PRODUCT LAUNCH

EPOCAST® 1622 FST A/B Adhesive

New Low-density, FST Epoxy Edge Filler from Huntsman Advanced Materials

Epocast® 1622 FST A/B is a two-component, flame-retardant epoxy syntactic/edge filler designed for interior applications such as insert potting, panel joining, reinforcement and edge closeout in honeycomb panel structures. Easy to mix and apply, Epocast® 1622 FST A/B is formulated to meet the flammability, smoke density and toxicity requirements of FAR 25.853. Available in 6 oz. Semco cartridges for easy use. Does not intentionally contain any Substances of Very High Concern (SVHC) as defined under REACH.

Key Features

Low Density of .77

High compressive strength of 8,500 psi @ 73° F

Thixotropic paste

15 minutes gel time

Room temp or heat cure

Key Benefits

Weight savings

High strength

Extrudable and gap filling

Short working time allows for high shop productivity

Flexible cure schedule

Contact your sales representative or distributor for a sample today.

Epocast® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all countries.

Huntsman Advanced Materials

10003 Woodloch Forest Dr.

The Woodlands, TX 77380

Tel: 888-564-9318

www.huntsman.com/advanced_materials

Distributed by: