

Technical Bulletin

JEFFCOOL[®] P156N INDUSTRIAL COOLANT AND HEAT TRANSFER FLUID

GENERIC NAME	Inhibited propylene glycol
DESCRIPTION	JEFFCOOL [®] P156N is an inhibited propylene glycol-based coolant for stationary engine and industrial applications. JEFFCOOL [®] P156N is a 60% by volume blend of JEFFCOOL [®] P150N coolant and deionized water.
APPLICATIONS	JEFFCOOL [®] P156N is a heavy-duty coolant for stationary engines in applications such as natural gas processing, irrigation, power generating systems, oilfield operations and portable air compressors. JEFFCOOL [®] P156N coolant is especially formulated to provide protection of cylinder liners from cavitation corrosion. JEFFCOOL [®] P156N coolant passes the ASTM D1384 corrosion test per the limits set in ASTM D3306, D4985 and D6210. Use in engines containing aluminum cylinder heads should be avoided. JEFFCOOL [®] P156N coolant is fully compatible with other propylene glycol-based products designed for similar applications.

SALES SPECIFICATIONS

<u>Property</u>	<u>Specifications</u>	<u>Test Method*</u>
Appearance	Slightly hazy and free of suspended solids	ST-30.1
Freeze point, as is		ASTM D3321
°C	-42 max.	
°F	-44 max.	
pH, 67 vol% solution	9.5 – 10.5	ASTM D-1287
Reserve Alkalinity, mL 0.1 N HCl using a 10 mL sample	5.8 – 9.1	ASTM D-1121
Specific gravity, 60/60°F	1.05 – 1.06	ASTM D-1122
Water, wt%	42 max.	ASTM D-1123

*Methods of Test are available from Huntsman Corporation upon request.

ADDITIONAL INFORMATION

Regulatory Information

See SDS for all regulatory information.

Typical Properties

Flash point, COC, °C (°F)	100 (212)
Color	Blue
Density, lb/US gal, 60°F	8.7
Viscosity, cSt, 20°C (68°F)	12
Water solubility, %	>10

TOXICITY AND SAFETY

For additional information on the toxicity and safe handling of this product, consult the Safety Data Sheet prior to use of this product.

HANDLING AND STORAGE

JEFFCOOL® P156N coolant may be stored in unlined carbon steel tanks and drums. If storage of concentrated JEFFCOOL® P156N coolant for periods over 12 months is desired, it is recommended that the storage vessels be constructed from aluminum, stainless steel, or lined carbon steel. Vinyl, epoxy, and phenolic linings are suitable.

For detailed information on the storage and handling of JEFFCOOL® P156N coolant, see our bulletin on "Storage and Handling of JEFFCOOL® Coolants."

AVAILABILITY

JEFFCOOL® P156N coolant is available in tank wagons and 55-gallon, non-returnable steel drums. Bulk and drum inventory of JEFFCOOL® P156N is available at select locations throughout the United States.

**Huntsman Corporation
Business Offices**

10003 Woodloch Forest Dr.
The Woodlands, TX 77380
(281) 719-6000

**Huntsman Advanced Technology
Center**

Technical Service
8600 Gosling Rd.
The Woodlands, TX 77381
(281) 719-7780

Samples 1-800-662-0924

www.huntsman.com

Copyright © 2014, 2015 Huntsman Corporation or an affiliate thereof. All rights reserved.

JEFFCOOL is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all countries.

Huntsman Corporation warrants only that its products meet the specifications stated in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, HUNTSMAN MAKES NO WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT OF ANY THIRD PARTY, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND ANY USER OF PRODUCTS DESCRIBED HEREIN SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE AND ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. Products may be toxic and require special precautions in handling. For all products described herein, the user should obtain detailed information on toxicity, together with proper shipping, handling, and storage procedures, and should comply with all applicable safety and environmental standards. The behavior, hazards and/or toxicity of the products referred to in this publication in manufacturing processes and their suitability in any given end-use environment are dependent upon various conditions such as chemical compatibility, temperature, and other variables, which may not be known to Huntsman. It is the sole responsibility of the user of such products to evaluate the manufacturing circumstances and the final products under actual end-use requirements and to adequately advise and warn future purchasers and users thereof.