


Technical Bulletin**E-GRADE® Propylene Glycol
(Electronic Grade)**

Generic: 1,2 propanediol

STRUCTURE**DESCRIPTION**

A relatively nontoxic liquid that is practically colorless, odorless, and tasteless.

APPLICATIONS

A high purity, low metals content propylene glycol intended for use in electronic applications requiring low metal content product.

SALES SPECIFICATIONS

Property	Specifications	Test Method *
Acidity (as acetic acid), wt.%	0.002 max.	ST-31.46, B
Appearance	Substantially free of suspended matter	ST-30.1
Chlorides, inorganic, ppm	0.5 max.	ST-4.44
Color, Pt-Co	10 max.	ST-30.12
Metals: (result of each), ppb aluminum, calcium, chromium, copper, iron, lead, magnesium, nickel, potassium, sodium, zinc	50 max.	AA, ICP, ICP-MS (ST-37.2, ICP-MS for potassium)
Propylene Glycol, area % by gas chromatography	99.5 min.	ST-35.102
Specific gravity, 25/25°C	1.0350 min. 1.0370 max.	ST-30.31
Specific resistance, 25°C, ohm-cm	3.0 x 10 ⁶ min.	ST4.79
Sulfate, ppm	60 max.	ST38.17
Water, wt.%	0.2 max.	ST-31.53

* Methods of test are available from Huntsman upon request.

ADDITIONAL INFORMATION

Regulatory Information	
DOT Classification	Not regulated
Freight Classification	Propylene Glycol
HMIS Code	See MSDS
CAS Number	57-55-6

Chemical Control Laws	
TSCA Inventory	Listed
WHMIS Classification	Not regulated
Canadian DSL	Listed
European EINECS	Listed
Australian AICS	Listed
Japanese MITI	Listed

Physical Properties	
Arsenic, ppm	1 max.
Boiling range ASTM, °C, IBP ASTM, °C, DP	185 min. 189 max.
Flash point, PMCC, °F	212
Freezing point, °C	< -76
Molecular weight	76
Refractive index, 25°C	1.4310 min. 1.4330 max.
Specific gravity, 25/25°C	1.0350 min. 1.0370 max.
Vapor pressure, 20°C, mm Hg	< 1
Viscosity, 20°C, cp	60
Water solubility, %	> 10
Weight, 20°C, lb/gal	8.64

PRODUCT SAFETY POLICY

It is the product safety policy of Huntsman Corporation to provide our customers with information on the safe handling and use of our products. The Material Safety Data Sheet (MSDS) should always be read and understood thoroughly before handling the product, and adequate safety procedures should be followed. Information on the toxicity, environmental, and industrial hygiene aspects of our products may be found in the MSDS. Precautionary measures include: use only with adequate ventilation; avoid breathing vapor, mist or gas; avoid contact with eyes, skin and clothing; keep container closed; wash thoroughly after handling.

HANDLING, STORAGE, AND SHIPPING PRECAUTIONS

E-GRADE® Propylene Glycol is a high-purity material, which must be handled with special precautions to avoid contamination. Stainless steel or aluminum vessels are recommended. For additional information on handling and storage of Propylene Glycol, please contact the Huntsman Technical Service Section. Product is available in barges, lined tank cars and dedicated tank trucks. Certain government regulations may apply at the time of shipment.

Huntsman Polyurethanes
10003 Woodloch Forest Drive,
The Woodlands,
Texas 77380, USA
Tel.: +1-281-719-6000
Fax.: +1-281-719-6416
web: www.huntsman.com/pu

For Your Protection**HEALTH AND SAFETY**

*The Safety and Health information in this data sheet does not contain sufficient detail for safe handling in all cases. For detailed safety and health information refer to the **Material Safety Data Sheet** for this product.*

EMERGENCY CALLS: Huntsman Emergency Response Center: 800-328-8501, 409-722-8381 / CHEMTREC - Spills, Leak, Fire 800-424-9300 (in USA and Canada)

IMPORTANT LEGAL NOTICE: Sales of the products described herein ("Product") are subject to the general terms and conditions of sale of Huntsman Corporation and its affiliates and subsidiaries (collectively, "Huntsman").

To the knowledge, information and belief of Huntsman, all the information and recommendations in this publication are accurate as of the date of publication.

WARRANTY:

Huntsman warrants that at the time and place of delivery all Products sold to a buyer of such Products shall conform to the specifications provided by Huntsman to such buyer of such Products.

DISCLAIMER AND LIMITATION OF LIABILITY:

EXCEPT AS SET FORTH ABOVE, HUNTSMAN MAKES NO OTHER WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT OF ANY THIRD PARTY, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND ANY BUYER OF PRODUCTS DESCRIBED HEREIN ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. Chemical or other properties purported to be typical of such Products, where stated herein, should be considered as representative of current production and should not be construed to be specifications of any such Products. In all cases, it is the sole responsibility of a buyer to determine the applicability of the information and recommendations contained in this publication and the suitability of any Product for its own particular purpose, and no statements or recommendations made herein are to be construed as a suggestion, recommendation, or authorization to take any action that would infringe any patent or other intellectual property right. A buyer or user of a Product is solely responsible for ensuring that its intended use of such Product does not infringe any third party's intellectual property rights. Huntsman's maximum liability for any claim related to the Products described herein or breach of an agreement associated therewith shall be limited to the purchase price of the Products or portion thereof to which such claim pertains. IN NO EVENT SHALL HUNTSMAN BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE DAMAGES, INCLUDING BUT NOT LIMITED TO ANY DAMAGES FOR LOST PROFITS OR BUSINESS OPPORTUNITIES OR DAMAGE TO REPUTATION.

WARNING:

The behaviour, hazardousness and/or toxicity of the Products referred to in this publication in manufacturing processes and their suitability in any given end-use environment are dependent upon various conditions such as chemical compatibility, temperature, and other variables, which may not be known to Huntsman. It is the sole responsibility of the buyer or user of such Products to evaluate the manufacturing circumstances and the final Product(s) under actual end-use requirements and to adequately advise and warn future purchasers and users thereof.

Products referred to in this publication may be hazardous and/or toxic and require special precautions in handling. A buyer should obtain Material Safety Data Sheets from Huntsman containing detailed information on hazardousness and/or toxicity of the products contained herein, together with proper shipping, handling and storage procedures, and should comply with all applicable safety and environmental standards. The Product(s) described herein have not been tested for, and is therefore not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for such uses.

Unless otherwise specified, Huntsman shall not be liable for or otherwise have any obligation to a buyer of any Products contained in this publication for any technical or other information or advice furnished by Huntsman in this publication.

E-GRADE® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all countries.

Copyright © 2009 Huntsman Corporation. All rights reserved.

For further information, please visit our website at: www.huntsman.com/pu November 16, 2009